



Technical Bulletin

2400 Boston Street, Suite 200, Baltimore, Maryland 21224
Phone: 410-675-2100 or 800-543-3840

Revised: 6/21/13

DAP® SMARTBOND™ Cleaner for Applicator Gun & Construction Adhesive

- Dissolves and removes uncured adhesive for fast and easy clean-up
- Cleans residual adhesive from inside of the Applicator Gun or other areas of spills or unwanted uncured adhesive
- Extends working life of the Applicator Gun
- Comes with two cleaning attachments

Packaging: Net Wt. 8.6 oz. (245 g)
Color: Clear
UPC Number: 0 70798 00044 5

Company Identification:

Manufactured For: DAP Products Inc., 2400 Boston St., Suite 200, Baltimore, Maryland 21224
Usage Information: Call 1-888-DAP-TIPS or visit dap.com & click on DAP Tips then "Ask the Expert".
Order Information: 800-327-3339
Fax Number: 410-558-1068

Product Description:

DAP® SMARTBOND™ Cleaner for Applicator Gun & Construction Adhesive is a pressurized cleaning solvent designed for use to dissolve and remove uncured construction adhesive from inside and outside of the Applicator Gun. It comes with a special adaptor that attaches to the SMARTBOND™ Construction Adhesive Applicator Gun to allow for easy cleaning. The detachable manual spray nozzle can be used to clean up spills and other areas of unwanted uncured adhesive.

Suggested Uses:

Cleans uncured construction adhesive from:

- Inside of the Applicator Gun
- Outside of the gun
- Surfaces and other areas of spills or uncured adhesive

Surface Preparation & Application:

SAFETY FIRST! PRODUCT IS EXTREMELY FLAMMABLE WHEN DISPENSING. Before using, read & understand all health & safety information/product use instructions found below.

1. Always wear safety glasses, gloves and protective clothing during use.
2. Replace canister or clean Applicator Gun immediately after canisters are emptied.
3. Unscrew emptied canister while holding in applicator trigger, being sure to point applicator tip in to an appropriate waste receptacle.
4. After removing spent adhesive can from applicator, clean uncured adhesive from basket adaptor by using the manual spray nozzle attached to the can. Be sure the indicator arrow on nozzle is pointed at the surface to be cleaned.
5. Firmly screw DAP® SMARTBOND™ Cleaner canister on to the Applicator Gun. Do not over tighten. Ensure that the threads are aligned to prevent leakage.
6. Adjust and set control knob to allow for maximum flow rate
7. Shake the canister well before using and intermittently during applicator cleaning.

8. Point applicator tip into an appropriate trash receptacle and pull the trigger to initiate flow of the Cleaner through the Applicator Gun. Release the trigger and repeat until discharge is clear and free of adhesive residue.
9. Remove the Cleaner and tighten down the control valve on the Applicator Gun for extended storage or attach a new canister of DAP® SMARTBOND™ Construction Adhesive to the Applicator Gun. The Cleaner may also be used to clean up wet adhesive on tools and surface spills. Test surfaces to ensure that the surface is compatible with the Cleaner before using. Do not use acetone or DAP® SMARTBOND™ Cleaner to clean skin.

Storage & Reuse:

Store the Applicator Gun attached to partially used adhesive can for up to one month. If longer storage is required, remove the Applicator Gun from the adhesive can and clean as directed. To prolong storage, it is recommended to purge the Applicator Gun weekly with a short discharge of adhesive foam into a waste receptacle. Once the Applicator Gun is removed from the adhesive can, the shelf life of DAP® SMARTBOND™ Subfloor Construction Adhesive is greatly diminished. It is not recommended to store partially used adhesive cans without the Applicator Gun attached.

Clean-up of Tools & Substrates:

Wipe off excess uncured adhesive with a paper towel or rag. Use DAP® SMARTBOND™ Cleaner for Applicator Gun & Construction Adhesive or acetone to dissolve and remove uncured construction adhesive from surfaces. Cured adhesive must be mechanically removed. Test surfaces to ensure surface is compatible with Cleaner before cleaning.

Uncured adhesive may be cleaned up with DAP® SMARTBOND™ Cleaner for Applicator Gun & Construction Adhesive or acetone. Cured adhesive cannot be removed with solvents. DO NOT use acetone or other solvents to remove product from skin. SKIN CONTACT: Wipe excess uncured adhesive off with a paper towel or rag immediately. Wash off remaining uncured adhesive immediately with soap and water. Remaining uncured residue may be removed with petroleum jelly or baby oil. For cured adhesive, first soak in warm soapy water and then apply petroleum jelly. Cured adhesive will wear off in time.

Typical Physical & Chemical Characteristics:

Volatile:	Acetone, Propane and Butane
Flash Point:	-143°F
Odor:	Solvent
Color:	Clear
Consistency:	Aerosol
Shelf Life:	18 months unopened
MSDS No.:	00010131004

Safety:

DANGER: CONTAINS ACETONE, PROPANE AND BUTANES. This product is flammable and may constitute a fire hazard if used improperly. Vapors may ignite explosively. Keep away from heat, sparks and flame. Extinguish all flames and pilot lights. Turn off stoves, heaters, electrical motors, and other sources of ignition during use and until vapor is gone. Do not smoke. If exposed to heat or direct sunlight, container may explode. Do not keep can in direct sunlight or high temperature areas, such as automobiles. Do not expose to heat or store can at temperatures above 120°F. Do not puncture, strike or burn can. Store out of direct sunlight, away from stoves, radiators and other heat sources. Vapors Harmful. May cause eye, skin, nose and throat irritation. May affect the brain or nervous system causing dizziness, headache or nausea. **NOTICE:** Reports have associated repeated and prolonged occupational over-exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling vapors may be harmful or fatal. Harmful or fatal if swallowed. Use only with adequate ventilation. Ensure fresh air entry during application and curing by opening all windows and doors and using fans or other means of ventilation. Do not breathe vapors. Do not get in eyes, on skin or clothing. Wear glove and eye protection. **FIRST AID:** SKIN CONTACT: Wash with soap and water. EYE CONTACT: Flood with large quantities of water. INHALATION: Remove to fresh air. INGESTION: DO NOT INDUCE VOMITING. Get medical attention immediately. If over-exposure occurs, call your poison control center at 1-800-222-1222. See Safety Data Sheet (SDS) for additional information. For a SDS contact your supplier or visit **dap.com**.

Limited Warranty:

DAP Products Inc. warrants that this product, when applied in accordance with DAP's label, technical bulletins and applicable industry standards, will be free from defects in material for 12 months from the date of purchase, but makes no warranty as to appearance or color. Since methods of application and on-site conditions are beyond DAP's control and could affect performance, DAP makes no other warranties, express or implied, including the warranties of Merchantability or Fitness for a Particular Use or Purpose. If a product defect is encountered, call 1-888-DAP-TIPS for warranty fulfillment. You must have your sales receipt and product container available when you call. DAP's sole liability is either to supply replacement product or refund the purchase price. DAP will in no event be liable for incidental or consequential damages.