



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® DYNAGRIP® Subfloor Construction Adhesive

PRODUCT DESCRIPTION

DAP® DYNAGRIP® SUBFLOOR adhesive is specifically formulated for subfloor and deck installation. This VOC compliant adhesive prevents floor squeaks and improves the structural performance of floor assembly when used properly. DYNAGRIP® SUBFLOOR is an easy to gun adhesive that delivers a strong durable bond.



PACKAGING	COLOR	UPC
10.3 fl oz (305 mL)	Light Tan	7079827514
28 fl oz (828 mL)	Light Tan	7079827515

KEY FEATURES & BENEFITS

- Prevents Floor Squeaks
- Easy to Gun – Reduces foreman fatigue
- Strong Durable Bond – Provides a long-lasting bond

PERFORMANCE CHARACTERISTICS

- Bonds wet, frozen & treated lumber
- VOC compliant
- Meets ASTM D3498 & APA AFG-01 specifications for subfloor installation

SUGGESTED USES

Adheres to:

- Concrete
- Dimensional Lumber
- Masonry
- Metal
- OSB
- Plywood



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

- Treated Lumber
- Wood

Recommended for:

- Subfloor & Deck Installation
- Wood-to-Wood Assemblies
- Glued Floor Systems

Not Recommended for:

- Bonding two non-porous materials
- Constant water exposure
- Foamboard installation
- Mirror installation
- Applications other than subfloor & deck installation

FOR BEST RESULTS

- Apply in temperatures above 40°F. Keep adhesive above 40°F for easier gunning.
- One surface must be porous.

NOTE: If using on concrete, concrete must be above grade, dry & fully cured (at least 28 days.)

APPLICATION

1. Surfaces must be clean, structurally sound and free of debris.
2. Precut and fit materials before applying adhesive.
3. Trim nozzle to desired bead size. 3/8" bead is recommended for subfloor applications.
4. Puncture inner foil seal.
5. Load cartridge into applicator gun.
6. Apply a continuous bead to joists, studs or backside of siding or panels. (See specific Application Tips below).
7. Within 15 minutes, position and press substrates firmly into place. If left open longer than 15 minutes, scrape off and reapply.
8. Install nails or screws within 15 minutes after positioning substrates in place.
9. Allow to dry for 24 hours before exposing to heavy traffic.

APPLICATION TIPS: TONGUE & GROOVE SUBFLOOR: Use a 3/8" continuous bead on joists. Use ample bead of adhesive in all grooved channels (remove excess squeezed out adhesive before it dries). Panel joints should not be tight. Allow 1/8" gap for expansion. Position and nail or screw within 30 minutes. Proper installation methods for subfloorings must be followed. **DECKS:** Use 1/4" adhesive bead on every joist for additional strength and to prevent squeaks. Nail planks at every other joist. Pre-drill nail holes.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Typical Uncured Physical Properties	
Appearance/Consistency	Smooth paste
Base Polymer:	Synthetic latex
Bead Color	Light tan
Weight % Solids	68% +/- 1%
Odor	Mild
Clean Up	Soap & water
Flash Point	212°F
Shelf Life	12 months
Coverage	10oz: ¼" bead yields 32 linear ft, 3/8" bead yields 14 linear ft 28oz: ¼" bead yields 86 linear ft, 3/8" beach yields 38 linear ft
Typical Application Properties	
Application Temperature Range:	40°F – 100°F
Tooling Time (Working Time)	15 minutes
Full Cure Time	7 days
Typical Cured Performance Properties	
Service Temperature Range:	0°F – 140°F
Gap Bridging	Up to 1/16"
VOC Content	< 50g/L
Calif. ARB VOC	<2% Wt/Wt

CLEAN UP & STORAGE

Uncured adhesive: use mineral spirits to clean up wet adhesive from surface and tools, following solvent manufacturers precautions. Do not use mineral spirits to clean skin. Cured adhesive must be cut or scraped away

SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at dap.com or by calling **1-888-DAP-TIPS**.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

WARRANTY

DAP will provide replacement product or refund sales price if product fails to perform when used as directed. Call 1-888-DAP-TIPS, with your sales receipt and product container available, to arrange for warranty fulfillment. DAP is not liable for incidental or consequential damages.

COMPANY IDENTIFICATION

Manufacturer: DAP Products Inc., 2400 Boston Street, Baltimore, Maryland 21224

Usage Information: Call **1-888-DAP-TIPS** or visit dap.com & click on "Ask the Expert"

Order Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com