



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® CrackSHOT® High Performance Spackling Paste

PRODUCT DESCRIPTION

DAP® CrackSHOT® Spackling Paste is a high-performance spackling for filling holes and cracks in surfaces such as drywall, plaster, wood, brick and stone. It can even be used for filling dents in metal doors and trim. Its ready-to-use smooth, white formula spreads easily for fast, professional repairs that will not crack, crumble or flake. It has a de-aired texture for excellent tooling and easy smoothing to a feather edge. CrackSHOT sands effortlessly. It can even be finger sanded – no sandpaper needed when sanding small nail holes or hammer dents in drywall. Just use finger to smooth dried spackling before painting. CrackSHOT provides unsurpassed paintable. It does not flash or gloss low sheen/flat paint. It accepts paint like bare drywall or other porous surfaces and provides a very smooth surface that disappears when painted. CrackSHOT cures quickly but has a long working time and will not gum up on knife.



PACKAGING	COLOR	UPC
Quart	White	7079812380

KEY FEATURES & BENEFITS

- Knife-grade formula
- Ideal for dents in metal doors & trim
- No shrinking
- Sands effortlessly
- Unsurpassed paintability – won't flash paint
- Interior/exterior use

SUGGESTED USES

Ideal for filling holes, cracks, dents and defects on:

- Drywall/plaster
- Wood
- Brick
- Stone
- Metal doors and trim



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

FOR BEST RESULTS

- Do not apply when temperatures are below 50°F.
- Do not apply outside if rain is expected within 24 hours.
- Do not use on floors or as a caulk, sealant or joint filler over cracks and joints where expansion and contraction may occur.
- **DO NOT USE AS A SKIM COAT.**
- For exterior applications, always topcoat with a quality paint prior to water exposure.
- If a textured finish is desired, add clean sand to spackling compound prior to application.
- Do not use for tuck pointing applications on brick.
- For larger areas to be patched on bare concrete, use a latex fortified Portland cement-based dry mix.

APPLICATION

1. Surface must be free of grease, oil and other foreign matter.
2. Stir thoroughly before use.
3. Apply with a clean putty knife.
4. For a smoother finish, dip putty knife in water and lightly smooth spackling.
5. One application is usually sufficient for small repairs. For repairs deeper than 1/4", apply two or more layers allowing spackling to dry between applications.
6. May be sanded or painted in 1 to 5 hours depending on temperature, humidity and depth of fill. Wet sanding is recommended to avoid generation of dust. Allow to dry after wet sanding.
7. Clean up with damp sponge before it skins over. Scrape or cut away excess cured.
8. Ensure that CrackSHOT Spackling Paste is thoroughly dry before sanding or applying oil-based paint. Spackling may be painted immediately upon drying with a quality latex paint.

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Consistency:	Paste
Vehicle:	Acrylic polymer
Volatile:	Water
Filler:	Inert filler
Odor:	Slight acrylic
Weight/Gallon:	15.6 pounds
Solids:	76% by weight
Application Temperature:	50°F or higher
Service Temperature:	0°F to 150°F
Shelf Life:	12 months
Freezing:	Freeze/thaw stable 5 cycles at 0°F



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

Drying Time:

1 to 5 hours depending on temperature, relative humidity and depth of fill

CLEAN UP & STORAGE

Wash tools immediately after use with water. Dried product must be cut, scraped or sanded away. Be sure container lid/cap is closed and tightly sealed. Store in a cool, dry place.

SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at dap.com or by calling **888-DAP-TIPS**.

WARRANTY

Limited Warranty:

If product fails to perform when used as directed, within one year of date of purchase, call 888-DAP-TIPS, with your sales receipt and product container available, for replacement product or sales price refund. DAP Products, Inc. will not be responsible for incidental or consequential damages.

COMPANY IDENTIFICATION

Manufacturer: DAP Products Inc., 2400 Boston Street, Baltimore, Maryland 21224

Usage Information: Call **888-DAP-TIPS** or visit dap.com & click on "Ask the Expert"

Order Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com