



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## DAP® PHENOPATCH® FLEXALL® Pre-Mixed Flexible All-Purpose Filler

### PRODUCT DESCRIPTION

DAP® PHENOPATCH® FLEXALL™ Flexible All-Purpose Filler is a pre-mixed, easy-to-use bridging and patching compound which dries to a flexible consistency. It can be used for patching any surface repairs which require thin bridging. It expands and contracts with surface movement to cover and prevent minor cracks from reappearing. Adheres to wood, metal, stucco, masonry, and most common building materials. Interior/exterior use.



PACKAGING	COLOR	UPC
Quart	Off-White	7079833011
Gallon	Off-White	7079833017

### KEY FEATURES & BENEFITS

- Pre-mixed, easy-to-use bridging & patching compound
- Dries flexible to prevent cracks from reappearing
- For repairing cracks in wood, metal, stucco, masonry and most common building materials
- Interior/exterior use

### SUGGESTED USES

Ideal for surface repairs which require thin, bridging applications and covering minor cracks

Adheres to:

- Wood
- Metal
- Stucco
- Masonry
- Most Common Building Materials

### FOR BEST RESULTS

- Do not apply in temperatures below 40°F.
- No mixing required. Do not thin product.



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

- Do not use for below waterline applications.
- **DO NOT USE AS A SKIM COAT**
- Do not use outside if rain or freezing temperatures are expected within 24 hours.

## APPLICATION

1. Surface must be clean, firm and free of debris and foreign material.
2. Apply compound with a clean putty knife or trowel.
3. Wide cracks require reinforcing with fiberglass tape.
4. Deep fills over 1/8" (3 mm) should be filled with DAP® PHENOPATCH® All-Purpose Spackling Paste (or in applications using stucco, DAP® Phenopatch® Stucco Patch) allowed to dry, and then bridged over with this compound.
5. For smoothest appearance, carefully tool product while wet. Sanding is not recommended
6. Allow compound to dry thoroughly (approximately 3 hours, depending on temperature, humidity and depth of fill) before reapplying or painting with latex or oil-based paints. Follow paint manufacturer's recommendations regarding priming and application.
7. **DO NOT USE AS A SKIM COAT.** For exterior applications always apply topcoat with a high quality exterior grade paint when fully cured and prior to water exposure.
8. Store away from extreme heat or cold.

## TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Consistency:	Smooth light paste
Vehicle:	Acrylic Latex
Volatile:	Water
Filler:	Inert Filler
Odor:	Mild
Weight/Gallon:	12.8 lbs./gal
Solids:	73%
Application Temperature:	Above 40°F to 100°F
Service Temperature:	-30°F to 180°F
Shelf Life:	12 months
Freezing:	Freeze/thaw stable 5 cycles at 0°F
Drying Time:	3 hours depending on temperature, relative humidity and depth of fill.
Paintable	Paintable with latex and oil-based paints. Follow paint manufacturer's recommendations regarding priming and application



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## CLEAN UP & STORAGE

Wash tools and hands immediately after use with water. Dried material must be cut or scraped away. Be sure container lid is closed and tightly sealed. Store in a cool, dry place away from extreme heat or cold.

## SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at [dap.com](http://dap.com) or by calling **888-DAP-TIPS**.

## WARRANTY

### **Limited Warranty:**

If product fails to perform when used as directed, within one year of date of purchase, call 888-DAP-TIPS, with your sales receipt and product container available, for replacement product or sales price refund. DAP Products, Inc. will not be responsible for incidental or consequential damages.

## COMPANY IDENTIFICATION

**Manufacturer:** DAP Products Inc., 2400 Boston Street, Baltimore, Maryland 21224

**Usage Information:** Call **888-DAP-TIPS** or visit [dap.com](http://dap.com) & click on "Ask the Expert"

**Order Information:** 800-327-3339 or [orders@dap.com](mailto:orders@dap.com)

**Fax Number:** 410-558-1068

**Also, visit the DAP website at [dap.com](http://dap.com)**