



## Safety Data Sheet

**24 Hour Emergency Phone Numbers**  
**Medical/Poison Control:**  
**In U.S.: Call 1-800-222-1222**

**Outside U.S.: Call your local poison control center**

**Transportation/National Response Center:**

**1-800-535-5053**  
**1-352-323-3500**

NOTE: The National Response Center emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.

IMPORTANT: Provide this information to employees, customers, and users of this product. Read this SDS before handling or disposing of this product. This product is covered by the OSHA Hazard Communication Standard and this document has been prepared in accordance with requirements of this standard. All abbreviated terms used in this SDS are further described in Section 16.

### 1. Identification

This Safety Data Sheet is available in American Spanish upon request.  
 Los Datos de Seguridad pueden obtenerse en Espanol si lo requiere.

<b>Product Name:</b>	Premium Polyurethane Construction Adhesive Sealant - Black	<b>Revision Date:</b>	2/7/2019
<b>Product UPC Number:</b>	070798188167	<b>Supercedes Date:</b>	6/19/2015
<b>Product Use/Class:</b>	Caulking Compound	<b>SDS No:</b>	00077350004
<b>Manufactured For</b>	DAP Products Inc. 2400 Boston Street Suite 200 Baltimore, MD 21224-4723 888-327-8477 (non - emergency matters)	<b>Preparer:</b>	Regulatory and Environmental Affairs
	SDS Coordinator: MSDS@dap.com		
	Emergency Telephone: 1-800-535-5053, 1-352-323-3500, 1-800-222-1222		

### 2. Hazards Identification

**GHS Classification**

Acute Tox. 4 Inhalation

**Symbol(s) of Product****Signal Word**

Warning

**Possible Hazards**

1% of the mixture consists of ingredients of unknown acute toxicity

**GHS HAZARD STATEMENTS**

Acute Toxicity, Inhalation, category 4 H332 Harmful if inhaled.

**GHS LABEL PRECAUTIONARY STATEMENTS**

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
 P271 Use only outdoors or in a well-ventilated area.  
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P312 Call a POISON CENTER or doctor/physician if you feel unwell.

### 3. Composition/Information on Ingredients

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt. %</u>	<u>GHS Symbols</u>	<u>GHS Statements</u>
Polymeric diphenylmethane diisocyanate	9016-87-9	80-100	GHS07	H332
Xylenes	1330-20-7	1-5	GHS02-GHS07	H226-312-315-332
Carbon black	1333-86-4	0.5-1.5	GHS02	H251
Titanium dioxide	13463-67-7	0.5-1.5	No Information	No Information

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

### 4. First-aid Measures

**FIRST AID - INHALATION:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

**FIRST AID - SKIN CONTACT:** Wash skin with soap and water for 15 minutes. Get medical aid if symptoms persist.

**FIRST AID - EYE CONTACT:** In case of contact, immediately flush eyes with large quantities of water for at least 15 minutes until irritation subsides. Get medical attention immediately.

**FIRST AID - INGESTION:** If swallowed, DO NOT INDUCE VOMITING. Get medical attention immediately.

### 5. Fire-fighting Measures

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** No Information

**SPECIAL FIREFIGHTING PROCEDURES:** Wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear. Use water spray to cool exposed surfaces.

**EXTINGUISHING MEDIA:** Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam

### 6. Accidental Release Measures

**ENVIRONMENTAL MEASURES:** No Information

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations. Scrape up dried material and place into containers.

### 7. Handling and Storage

**HANDLING:** KEEP OUT OF REACH OF CHILDREN! DO NOT TAKE INTERNALLY. Avoid breathing vapor and contact with eyes, skin and clothing. Use only with adequate ventilation. Ensure fresh air entry during application and drying. Wash thoroughly after handling. Contains isocyanates. See information supplied by the manufacturer. Persons allergic to isocyanates, and particularly those suffering from asthma or other respiratory conditions, should not work with isocyanates.

**STORAGE:** Avoid excessive heat and freezing. Store away from caustics and oxidizers.

## 8. Exposure Controls/Personal Protection

### Ingredients with Occupational Exposure Limits

<u>Chemical Name</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH-TLV STEL</u>	<u>OSHA PEL-TWA</u>	<u>OSHA PEL-CEILING</u>
Polymeric diphenylmethane diisocyanate	N.E.	N.E.	N.E.	N.E.
Xylenes	100 ppm TWA	150 ppm STEL	100 ppm TWA, 435 mg/m <sup>3</sup> TWA	N.E.
Carbon black	3 mg/m <sup>3</sup> TWA inhalable particulate matter	N.E.	3.5 mg/m <sup>3</sup> TWA	N.E.
Titanium dioxide	10 mg/m <sup>3</sup> TWA	N.E.	15 mg/m <sup>3</sup> TWA total dust	N.E.

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation  
Sk = Skin Sensitizer N.E. = Not Established

### Personal Protection



**RESPIRATORY PROTECTION:** No personal respiratory protective equipment normally required. If concentrations exceed the exposure limits specified, use of a NIOSH-approved supplied air respirator is recommended. Where the protection factor is exceeded, use of a Self Contained Breathing Apparatus (SCBA) may be necessary. A respiratory protection program that meets the OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.



**SKIN PROTECTION:** Wear solvent impervious gloves.



**EYE PROTECTION:** Goggles or safety glasses with side shields.



**OTHER PROTECTIVE EQUIPMENT:** Provide eyewash and solvent impervious apron if body contact may occur.



**HYGIENIC PRACTICES:** Wash hands before breaks and at the end of workday. Remove and wash contaminated clothing before re-use.

## 9. Physical and Chemical Properties

<b>Appearance:</b>	Colored	<b>Physical State:</b>	Paste
<b>Odor:</b>	Slight	<b>Odor Threshold:</b>	Not Established
<b>Density, g/cm<sup>3</sup>:</b>	1.40 - 1.40	<b>pH:</b>	Not Applicable
<b>Freeze Point, °C:</b>	Not Established	<b>Viscosity (mPa.s):</b>	Not Established
<b>Solubility in Water:</b>	No Information	<b>Partition Coeff., n-octanol/water:</b>	Not Established
<b>Decomposition Temperature, °C:</b>	Not Established	<b>Explosive Limits, %:</b>	N.E. - N.E.
<b>Boiling Range, °C:</b>	100 - 100	<b>Auto-Ignition Temperature, °C</b>	Not Established
<b>Minimum Flash Point, °C:</b>	100	<b>Vapor Pressure, mmHg:</b>	Not Established
<b>Evaporation Rate:</b>	Slower Than n-Butyl Acetate	<b>Flash Method:</b>	Seta Closed Cup
<b>Vapor Density:</b>	Heavier Than Air	<b>Flammability, NFPA:</b>	Non-Flammable
<b>Combustibility:</b>	Does not support combustion		

(See "Other information" Section for abbreviation legend)

(If product is an aerosol, the flash point stated above is that of the propellant.)

## 10. Stability and Reactivity

**STABILITY:** Stable under recommended storage conditions.

**CONDITIONS TO AVOID:** Excessive heat and freezing.

**INCOMPATIBILITY:** Incompatible with strong bases and oxidizing agents.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Normal decomposition products, i.e., CO<sub>x</sub>, NO<sub>x</sub>.

## 11. Toxicological Information

**EFFECT OF OVEREXPOSURE - INHALATION:** Vapors may be irritating to eyes, nose, throat, and lungs. Inhalation of high concentrations may cause headache, nausea, and dizziness.

**EFFECT OF OVEREXPOSURE - SKIN CONTACT:** May cause sensitization by skin contact. May cause localized irritation, reddening or swelling. Prolonged or repeated exposure may lead to sensitization and/or contact dermatitis. This product has strong adhesive-like characteristics and will adhere aggressively to skin and other surfaces. If accidental contact occurs, follow the appropriate first-aid procedure described in Section 4 of this SDS.

**EFFECT OF OVEREXPOSURE - EYE CONTACT:** Direct eye contact may cause irritation.

**EFFECT OF OVEREXPOSURE - INGESTION:** Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

**CARCINOGENICITY:** No Information

**EFFECT OF OVEREXPOSURE - CHRONIC HAZARDS:** Repeated or prolonged exposure may cause respiratory system damage. Repeated contact may cause allergic reactions in very susceptible persons.

**PRIMARY ROUTE(S) OF ENTRY:** Skin Contact, Inhalation

### Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
9016-87-9	Polymeric diphenylmethane diisocyanate	49000 mg/kg Rat	>9400 mg/kg Rabbit	N.I.
1330-20-7	Xylenes	3500 mg/kg Rat	1700 mg/kg Rabbit	29.08 mg/L Rat
1333-86-4	Carbon black	>15400 mg/kg Rat	N.I.	N.I.
13463-67-7	Titanium dioxide	>10000 mg/kg Rat	>5000 mg/kg Rabbit	>20 mg/L

N.I. = No Information

## 12. Ecological Information

**ECOLOGICAL INFORMATION:** No Information

## 13. Disposal Information

**DISPOSAL INFORMATION:** This product does not meet the definition of a hazardous waste according to U.S. EPA Hazardous Waste Management Regulation, 40 CFR Section 261. Dispose as hazardous waste according to all local, state, federal and provincial regulations. State and Local regulations/restrictions are complex and may differ from Federal regulations. Responsibility for proper waste disposal is with the owner of the waste. Liquids cannot be disposed of in a landfill.

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations. Scrape up dried material and place into containers.

## 14. Transport Information

**SPECIAL TRANSPORT PRECAUTIONS:** As packaged:

Not a dangerous good under International Air Transport (IATA).

Not a dangerous good under International Maritime Transport (IMO).

Not a dangerous good under Canada Transport of Dangerous Goods (TDG).

**DOT UN/NA Number:** N.A.  
**DOT Proper Shipping Name:** Not Regulated  
**DOT Technical Name:** N.A.  
**DOT Hazard Class:** N.A.  
**Hazard SubClass:** N.A.  
**Packing Group:** N.A.

## 15. Regulatory Information

### SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

### TOXIC SUBSTANCES CONTROL ACT:

All ingredients in this product are either on TSCA inventory list, or otherwise exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

## 16. Other Information

**Revision Date:** 2/7/2019 **Supersedes Date:** 6/19/2015

**Reason for revision:** Revision Description Changed  
 Substance and/or Product Properties Changed in Section(s):  
 01 - Product Information  
 02 - Hazards Identification  
 05 - Flammability Information  
 08 - Exposure Controls/Personal Protection  
 09 - Physical & Chemical Information  
 11 - Toxicological Information  
 13 - Disposal Information  
 14 - Transportation Information  
 15 - Regulatory Information  
 Substance Chemical Name Changed  
 Substance Regulatory CAS Number Changed  
 Substance Hazard Threshold % Changed  
 Revision Statement(s) Changed

**Datasheet produced by:** Regulatory Department

### HMIS Ratings:

Health:	Flammability:	Reactivity:	Personal Protection:
2	1	0	X

**VOC Less Water Less Exempt Solvent, g/L:** 35.7

**VOC Material, g/L:** 36

**VOC as Defined by California Consumer Product Regulation, Wt/Wt%:** 2.6

**VOC Actual, Wt/Wt%:** 2.6

### Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H226	Flammable liquid and vapour.
H251	Self-heating: may catch fire.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H332	Harmful if inhaled.

**Icons for GHS Pictograms shown in Section 3 describing each ingredient:**

GHS02



GHS07



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

DAP believes the data and statements contained herein are accurate as of the date hereof. They are offered in good faith as typical values and not as a product specification. NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE WITH REGARD TO THE INFORMATION HEREIN PROVIDED OR THE PRODUCT TO WHICH THE INFORMATION REFERS. Since this document is intended only as a guide to the appropriate use and precautionary handling of the referenced product by a properly trained person, it is therefore the responsibility of the user to (i) review the recommendations with due consideration for the specific context of the intended use and (ii) determine if they are appropriate.