



# Technical Bulletin

2400 Boston Street, Suite 200, Baltimore, Maryland 21224

Phone: 410-675-2100 or 800-543-3840

Revised: 5/20/07

## DAP® KWIK SEAL® Grout Repair

- Ready to use
- Stain resistant
- No sealing required
- Easy water clean-up
- Non-sanded

**Packaging:** 4 fluid ounces (118 mL)

**Color:** Arctic White

**UPC Number:** 0 70798 18372 8

### Company Identification:

Manufacturer: DAP Products Inc., 2400 Boston St., Baltimore, Maryland 21224

Usage Information: DAP HELPLINE: 888-DAP-TIPS, 9:00 am to 7:00 pm EST.

Order Information: 800-327-3339

Also, visit the DAP website at **www.dap.com**.

### Product Description:

**DAP® KWIK SEAL® Grout Repair** is a ready-to-use, water-resistant compound for small interior ceramic and mosaic wall tile installation and repair jobs. It offers superior stain resistance and requires no sealing. Cleans up easily with soap and water. Non-sanded.

### Suggested Uses:

**Ideal for Grouting:** Ceramic and mosaic wall tiles with joints up to 1/8" wide.

### Performance Characteristics:

- Ready to use – needs no mixing or additives
- Superior stain resistance
- Water resistant
- Easy water clean-up

### Surface Preparation & Application:

#### INSTALLATION INSTRUCTIONS:

1. Clean and dry tile and tile joints.
2. Knead tube before using.
3. Remove cap and cut nozzle at 45° angle to desired bead size.
4. Apply grout evenly to each joint. Work thoroughly into each joint with sponge or float.
5. Wait 30 minutes for grout to set. Remove excess grout by pulling a damp cloth diagonally across tiles.
6. Wait until grout firmly sets (approximately 1 hour), then buff with clean, dry cloth.
7. Allow area to dry 72 hours before exposing to water.

8. Clean up with water before grout dries.
9. Reseal tube with cap for next use.

### **REPAIR INSTRUCTIONS:**

1. Chisel out 1/16" of old grout.
2. Scrub surface thoroughly with white kitchen cleanser.
3. Follow installation instructions above.

### ***FOR BEST RESULTS***

- Store away from extreme heat or cold.
- Allow area to dry 72 hours before exposing to water.
- Not recommended for quarry tile, pavers, slate, non-porous stone and Mexican tiles.

### **Physical & Chemical Characteristics:**

Working Time:	Approximately 15 minutes
Initial Cure:	Approximately 1 hour
Final Cure:	Approximately 72 hours
Clean up:	With soapy water immediately after use.
MSDS No:	000 10052 001

### **Clean Up:**

Clean up with water while grout is still workable.

### **Safety:**

See product label or Material Safety Data Sheet for safety information. You can request an MSDS by visiting our website at [www.dap.com](http://www.dap.com) or calling 888-DAP-TIPS.

### **Warranty Information:**

If not satisfied with product performance when used as directed, return used container and sales receipt to DAP Products Inc., Technical Customer Service, 2400 Boston St., Baltimore, MD 21224 for product replacement or sales price refund. DAP will not be liable for incidental or consequential damages.